



6"

WATER LUBRICATED C.I. KLASSIC SUBMERSIBLE MOTOR

Unnati UW6 series submersible motors are water Lubricated designed for installation in 6" diameter or larger water wells. These motors can be easily rewound and repaired.

Unnati Submersible Motors are robust rewindable and pre-filled with clean water mixed with anti-corrosion fluid. The stator winding is of PVC or Poly Propylene insulated copper winding wires. It features water lubricated radial and thrust bearings. Dynamically balanced rotor of these Unnati UW6 Series submersible motors maintain uniform clearance to give better efficiency and increase the life cycle of the water lubricated bush bearings. Specially designed high performance thrust bearings are used to withstand high axial thrust loads.

Pressure equalizing rubber diaphragm is provided to guard against pressure and volume variations due to thermal expansion of water inside the motor. Motor is sealed by "O" rings, shaft seals and sand guards to prevent leakage of motor lubricants and ingress of well water, sand and fibre particles in to the motor. Mounting dimension of motors are in accordance with "NEMA" standard.



PRODUCT SPECIFICATION

- Rewindable
- Connecting piece : Graded C.I Casting with Epoxy paint.
- Upper & Lower Housing : Cast iron Graded with Epoxy paint.
- Motor base : Graded C.I Casting with Epoxy paint.
- Stator shell : S S 304
- Motor shaft : S S 420
- Winding wire : Poly Propylene or PVC insulated
- Shaft extension and coupling dimensions : As per "NEMA"

Standards

- Degree of protection : IP 68
- Max water temperature : 35° C
- Nos. of Start per Hour : Max 20 at regular intervals.
- Voltage variation : +6% / -10% at rated voltage.
- Max depth immersion : 500 metres.
- Motor cable length : 3.0 metres (3 core / 4 core)
- Maximum Outer Dia : 142 mm
- Power Range : 4.0 kW - 45 kW - Three Phase
- Versions :
- A.C. Three phase : 380-400-415 volt - 50 HZ
- Direct Online (D.O.L.) : 4.0 kW - 45 kW
- Star Delta (S.D.) : 7.5 kW - 45 kW
- Speed : 2900 RPM
- Type of Duty : S1 (Continuous)

PRODUCT FEATURE

- Unnati UW6 Submersible Motors are robust Rewindable and pre-filled with clean water mixed with anti-corrosion fluid.
- Stator shell with corrosion resistant Stainless Steel.
- Bearing : Water lubricated radial and thrust bearing.
- Shaft extension made of Stainless Steel AISI 420.
- High efficiency electrical design for Lower Operating Cost.
- Pressure compensation diaphragm.

PRODUCT APPLICATION

"Unnati" prime mover Submersible Motors are suitable to couple with deep well Submersible Pump used for :

- Residential Purpose
- Irrigation
- Fountains
- Industrial water supply
- Pressure Boosting Units
- Gardens & Horticulture
- Drip & Sprinkler Systems
- Mining Industries
- Oil & Gas Industries
- De-watering
- Fire Fighting





WATER LUBRICATED C.I. KLASSIC SUBMERSIBLE MOTOR

SR. NO.	DESCRIPTION	QTY.
1	MOTOR BASE	1
2	BREATHER DIAPHRAGM	1
3	DIAPHRAGM SPRING	1
4	LOWER PART	1
5	ROCKER SUPPORT	1
6	THRUST BEARING	1
7	LOWERT BEARING HOUSING	1
8	BEARING BUSH	4
9	STATOR STAMPING	AS PER S.L.
10	STATOR TUBE	1
11	COLLAR	2
12	ROTOR	1
13	UPPER BEARING HOUSING	1
14	CONNECTING PIECE	1
15	UPPER CLAMPING STUD	4
16	LOWER CLAMPING STUD	4
17	INSULATED WINDING WIRE	

Model	P _n		Motor Length (mm)	Net Weight (kg)
	kW	HP		
UW6TP0055H5CIKL	4.00	5.50	650	55
UW6TP0075H5CIKL	5.50	7.50	700	58
UW6TP0100H5CIKL	7.50	10.00	750	63
UW6TP0125H5CIKL	9.30	12.50	760	66
UW6TP0150H5CIKL	11.00	15.00	800	70
UW6TP0175H5CIKL	13.00	17.50	850	74
UW6TP0200H5CIKL	15.00	20.00	925	80
UW6TP0250H5CIKL	18.50	25.00	975	85
UW6TP0300H5CIKL	22.00	30.00	1098	98
UW6TP0350H5CIKL	26.50	36.00	1173	104
UW6TP0400H5CIKL	30.00	40.00	1223	111
UW6TP0500H5CIKL	37.50	50.00	1273	117
UW6TP0600H5CIKL	45.00	60.00	1373	128

P_n = Rated Output



